33178 - RESTAURO

33178 Madder (Alizarin) Deep

Revision nr.5 Dated 15/11/2018 Printed on 15/11/2018 Page n. 1 / 10 Replaced revision:4 (Dated 14/09/2018)

# Safety Data Sheet

According to Annex II to REACH - Regulation 2015/830

1.1. Product identifier		
Code:	33178	
Product name	RESTAURO	33178 Madder (Alizarin) Deep
1.2. Relevant identified uses of the substance	or mixture and uses adv	ised against
Intended use	Restauro varnish o	colour.
1.3. Details of the supplier of the safety data s	heet	
Name	INDUSTRIA MAIMI	ERI S.p.A.
Full address	Via Gianni Maimer	i, 1
District and Country	20060 Mediglia	(MI)
	Italia	
	Tel. +39 02 906	981
	Fax +39 02 906	98999
e-mail address of the competent person		
responsible for the Safety Data Sheet	schedesicurezza@	pmaimeri.it
Product distribution by:		ERI S.P.A. VIA G.MAIMERI 1 20060 BETTOLINO DI MEDIGLIA (MI)
	ITALY	
1.4. Emergency telephone number		
For urgent inquiries refer to	Australia : 131126	
	USA: 1 800 222 12	22
	Regno Unito NHS	Direct (UK): +44 (0) 845 46 47

# **SECTION 2. Hazards identification**

# 2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2015/830.

Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:		
Flammable liquid, category 3	H226	Flammable liquid and vapour.
Specific target organ toxicity - repeated exposure,	H372	Causes damage to organs through prolonged or repeated
category 1		exposure.
Eye irritation, category 2	H319	Causes serious eye irritation.
Skin irritation, category 2	H315	Causes skin irritation.
Skin sensitization, category 1	H317	May cause an allergic skin reaction.
Specific target organ toxicity - single exposure, category 3	H336	May cause drowsiness or dizziness.
Hazardous to the aquatic environment, chronic toxicity, category 2	H411	Toxic to aquatic life with long lasting effects.

## 2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:



ΕN

# 33178 - RESTAURO

33178 Madder (Alizarin) Deep

Revision nr.5 Dated 15/11/2018 Printed on 15/11/2018 Page n. 2 / 10 Replaced revision:4 (Dated 14/09/2018)

## SECTION 2. Hazards identification ... / >>

Signal words:	Danger
Hazard statements:	
H226	Flammable liquid and vapour.
H372	Causes damage to organs through prolonged or repeated exposure.
H319	Causes serious eye irritation.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.
Precautionary statemer	nts:
P501	Dispose of contents / container to in accordance with local and national norms
P102	Keep out of reach of children.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P280	Wear protective gloves/ protective clothing / eye protection / face protection.
P271	Use only outdoors or in a well-ventilated area.
P101	If medical advice is needed, have product container or label at hand.
P405	Store locked up.
Contains:	Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) Turpentine Essence

### 2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

# **SECTION 3. Composition/information on ingredients**

## 3.2. Mixtures

Contains:

Identification	x = Conc. %		Classification 1272/2008 (CLP)
Hydrocarbons	, C9-C12, n-alkanes, is	oalkanes,	cyclics, aromatics (2-25%)
CAS	64742-82-1 27 ≤ x <	28,5	Flam. Liq. 3 H226, STOT RE 1 H372, Asp. Tox. 1 H304, STOT SE 3 H336, Aquatic Chronic 2 H411, EUH066, Classification note according to Appen VI to the CLB Regulation: B
EC INDEX	919-446-0		Classification note according to Annex VI to the CLP Regulation: P
Reg. no.	01-2119458049-33		
<b>Turpentine Es</b>	sence		
CAS	8006-64-2 13,5 ≤ x	< 15	Flam. Liq. 3 H226, Acute Tox. 4 H302, Acute Tox. 4 H312, Acute Tox. 4 H332, Asp. Tox. 1 H304, Eye Irrit. 2 H319, Skin Irrit. 2 H315, Skin Sens. 1 H317, Aquatic Chronic 2 H411
EC	232-350-7		•
INDEX	650-002-00-6		
Reg. no.	01-2119553060-53		
9,10-Anthrace	nedione,1,2 dihydrxy		
CAS EC INDEX	72-48-0 10 ≤ x < 200-782-5	11,5	Eye Irrit. 2 H319, Skin Irrit. 2 H315

The full wording of hazard (H) phrases is given in section 16 of the sheet.

# **SECTION 4. First aid measures**

## 4.1. Description of first aid measures

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. If problem persists, seek medical advice.

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention immediately. Wash contaminated clothing before using it again.

INHALATION: Remove to open air. If the subject stops breathing, administer artificial respiration. Get medical advice/attention immediately. INGESTION: Get medical advice/attention immediately. Do not induce vomiting. Do not administer anything not explicitly authorised by a doctor.

# 33178 - RESTAURO

33178 Madder (Alizarin) Deep

ΕN

# SECTION 4. First aid measures ..../>>

## 4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

## 4.3. Indication of any immediate medical attention and special treatment needed

Information not available

# **SECTION 5. Firefighting measures**

# 5.1. Extinguishing media

## SUITABLE EXTINGUISHING EQUIPMENT

Extinguishing substances are: carbon dioxide, foam, chemical powder. For product loss or leakage that has not caught fire, water spray can be used to disperse flammable vapours and protect those trying to stem the leak.

UNSUITABLE EXTINGUISHING EQUIPMENT

Do not use jets of water. Water is not effective for putting out fires but can be used to cool containers exposed to flames to prevent explosions.

### 5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE Excess pressure may form in containers exposed to fire at a risk of explosion. Do not breathe combustion products.

## 5.3. Advice for firefighters

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations. SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

# SECTION 6. Accidental release measures

# 6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

Send away individuals who are not suitably equipped. Use explosion-proof equipment. Eliminate all sources of ignition (cigarettes, flames, sparks, etc.) from the leakage site.

## 6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

### 6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

## 6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

# **SECTION 7. Handling and storage**

# 7.1. Precautions for safe handling

Keep away from heat, sparks and naked flames; do not smoke or use matches or lighters. Without adequate ventilation, vapours may accumulate at ground level and, if ignited, catch fire even at a distance, with the danger of backfire. Avoid bunching of electrostatic charges. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in

# 33178 - RESTAURO

# 33178 Madder (Alizarin) Deep

ΕN

## SECTION 7. Handling and storage ... / >>

which people eat. Avoid leakage of the product into the environment.

#### 7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store in a well ventilated place, keep far away from sources of heat, naked flames and sparks and other sources of ignition. Keep containers away from any incompatible materials, see section 10 for details.

#### 7.3. Specific end use(s)

Information not available

# **SECTION 8. Exposure controls/personal protection**

## 8.1. Control parameters

EU

Regulatory References:

OEL EUDirective (EU) 2017/2398; Directive (EU) 2017/164; Directive 2009/161/EU; Directive 2006/15/EC;<br/>Directive 2004/37/EC; Directive 2000/39/EC; Directive 91/322/EEC.TLV-ACGIHACGIH 2018

				Turpent	ine Essence				
Threshold Limit	Value								
Туре	Country	TWA/8h		STEL/15	min				
		mg/m3	ppm	mg/m3	ppm				
OEL	EU	112	20						
TLV-ACGIH		111	20				(sens), A4		
Predicted no-effe			С						
Normal value i							88	µg/L	
Normal value i							88	µg/L	
Normal value f							227	mg/kg	
Normal value f			-				227	mg/kg	
Normal value f	,		ase				NPI		
	Normal value of STP microorganisms 66 mg/l								
Normal value for the food chain (secondary poisoning) VND									
Normal value for the terrestrial compartment 45 mg/kg									
Health - Derived									
		ects on cons				Effects on wor			
Route of expos			ute	Chronic	Chronic	Acute	Acute	Chronic	Chronic
	loca	al sy:	stemic	local	systemic	local	systemic	local	systemic
Oral									
Inhalation								5.98	
Skin						161			

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified.

### 8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

Exposure levels must be kept as low as possible to avoid significant build-up in the organism. Manage personal protective equipment so as to guarantee maximum protection (e.g. reduction in replacement times).

HAND PROTECTION

Protect hands with category III work gloves (see standard EN 374).

The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

SKIN PROTECTION

Wear category III professional long-sleeved overalls and safety footwear (see Directive 89/686/EEC and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

Consider the appropriateness of providing antistatic clothing in the case of working environments in which there is a risk of explosion. EYE PROTECTION

33178 - RESTAURO

# 33178 Madder (Alizarin) Deep

## SECTION 8. Exposure controls/personal protection .../>>

Wear airtight protective goggles (see standard EN 166).

In the presence of risks of exposure to splashes or squirts during work, adequate mouth, nose and eye protection should be used to prevent accidental absorption.

RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, use a mask with a type A filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529. ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

Product residues must not be indiscriminately disposed of with waste water or by dumping in waterways.

# **SECTION 9.** Physical and chemical properties

## 9.1. Information on basic physical and chemical properties

Appearance	paste
Colour	dark red
Odour	MASTIC RESIN
Odour threshold	Not applicable
pH	Not applicable
Melting point / freezing point	Not applicable
Initial boiling point	Not available
Boiling range	Not applicable
Flash point	23 ≤ T ≤ 60 °C
Evaporation Rate	Not applicable
Flammability of solids and gases	not applicable
Lower inflammability limit	Not applicable
Upper inflammability limit	Not applicable
Lower explosive limit	Not applicable
Upper explosive limit	Not applicable
Vapour pressure	Not applicable
Vapour density	Not applicable
Relative density	1.3
Solubility	INSOLUBLE, DILUTE WITH TURPENTINE ESSENCE
Partition coefficient: n-octanol/water	Not applicable
Auto-ignition temperature	Not applicable
Decomposition temperature	Not applicable
Viscosity	1.500.000-3.000.000 cps
Explosive properties	not applicable
Oxidising properties	not applicable
or research	

# 9.2. Other information

VOC (Directive 2010/75/EC) :

42,02 % - 546,28 g/litre

# **SECTION 10. Stability and reactivity**

## 10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

#### 10.2. Chemical stability

The product is stable in normal conditions of use and storage.

## 10.3. Possibility of hazardous reactions

The vapours may also form explosive mixtures with the air.

# 33178 - RESTAURO

33178 Madder (Alizarin) Deep

Revision nr.5 Dated 15/11/2018 Printed on 15/11/2018 Page n. 6 / 10 Replaced revision:4 (Dated 14/09/2018) ΕN

# SECTION 10. Stability and reactivity ..../>>

### 10.4. Conditions to avoid

Avoid overheating. Avoid bunching of electrostatic charges. Avoid all sources of ignition.

#### 10.5. Incompatible materials

Information not available

### 10.6. Hazardous decomposition products

In the event of thermal decomposition or fire, gases and vapours that are potentially dangerous to health may be released.

# **SECTION 11. Toxicological information**

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification. It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

#### 11.1. Information on toxicological effects

Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

Information not available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Information not available

Interactive effects

Information not available

ACUTE TOXICITY

LC50 (Inhalation) of the mixture: LD50 (Oral) of the mixture: LD50 (Dermal) of the mixture: > 20 mg/l >2000 mg/kg >2000 mg/kg

Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) LD50 (Oral) > 5000 mg/kg LD50 (Dermal) > 4 mg/Kg

#### SKIN CORROSION / IRRITATION

Causes skin irritation

SERIOUS EYE DAMAGE / IRRITATION

Causes serious eye irritation

RESPIRATORY OR SKIN SENSITISATION

Sensitising for the skin

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

REPRODUCTIVE TOXICITY

# 33178 - RESTAURO

33178 Madder (Alizarin) Deep

Revision nr.5 Dated 15/11/2018 Printed on 15/11/2018 Page n. 7 / 10 Replaced revision:4 (Dated 14/09/2018)

#### SECTION 11. Toxicological information ... / >>

Does not meet the classification criteria for this hazard class

STOT - SINGLE EXPOSURE

May cause drowsiness or dizziness

STOT - REPEATED EXPOSURE

Causes damage to organs

ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class Viscosity: 1.500.000-3.000.000 cps

# **SECTION 12. Ecological information**

This product is dangerous for the environment and is toxic for aquatic organisms. In the long term, it have negative effects on acquatic environment.

#### 12.1. Toxicity

Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)LC50 - for Fish< 30 mg/l/96h</td>EC50 - for Crustacea< 22 mg/l/48h</td>EC50 - for Algae / Aquatic Plants< 10 mg/l/72h</td>

#### 12.2. Persistence and degradability

Information not available

#### 12.3. Bioaccumulative potential

Information not available

#### 12.4. Mobility in soil

Information not available

#### 12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

#### 12.6. Other adverse effects

Information not available

# **SECTION 13. Disposal considerations**

## 13.1. Waste treatment methods

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

Waste transportation may be subject to ADR restrictions.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

# **SECTION 14. Transport information**

# 14.1. UN number

ADR / RID, IMDG, IATA: 1263

# 33178 - RESTAURO

# 33178 Madder (Alizarin) Deep

3

Revision nr.5 Dated 15/11/2018 Printed on 15/11/2018 Page n. 8 / 10 Replaced revision:4 (Dated 14/09/2018)

## SECTION 14. Transport information .... / >>

### 14.2. UN proper shipping name

ADR / RID:PAINT or PAINT RELATED MATERIALIMDG:PAINT or PAINT RELATED MATERIAL (Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) )IATA:PAINT or PAINT RELATED MATERIAL

## 14.3. Transport hazard class(es)

ADR / RID:	Class: 3	Label: 3
IMDG:	Class: 3	Label: 3
ΙΑΤΑ:	Class: 3	Label: 3

#### 14.4. Packing group

ADR / RID, IMDG, IATA: III

## 14.5. Environmental hazards

ADR / RID:	Environmentally Hazardous

NO

IMDG: Marine Pollutant

IATA:

For Air transport, environmentally hazardous mark is only mandatory for UN 3077 and UN 3082.

### 14.6. Special precautions for user

ADR / RID:

IATA:

Special Provision: -EMS: F-E, <u>S-E</u> Cargo: Pass.: Special Instructions:

HIN - Kemler: 30

Limited Quantities: 5 L

Limited Quantities: 5 L Maximum quantity: 220 L Maximum quantity: 60 L A3, A72, A192 Tunnel restriction code: (D/E)

Packaging instructions: 366 Packaging instructions: 355

#### 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Information not relevant

# SECTION 15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso Category - Directive 2012/18/EC:

P5c-E2

# Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

Product Point

3 - 40

Substances in Candidate List (Art. 59 REACH) On the basis of available data, the product does not contain any SVHC in percentage greater than 0,1%.

Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to (EC) Reg. 649/2012:

@EPY 9.8.3 - SDS 1004.11

ΕN

# 33178 - RESTAURO

# 33178 Madder (Alizarin) Deep

## SECTION 15. Regulatory information ..../>>

## None

Substances subject to the Rotterdam Convention:

Substances subject to the Stockholm Convention:

None

Healthcare controls

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

#### 15.2. Chemical safety assessment

No chemical safety assessment has been processed for the mixture and the substances it contains.

# **SECTION 16. Other information**

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Flam. Liq. 3	Flammable liquid, category 3
Acute Tox. 4	Acute toxicity, category 4
STOT RE 1	Specific target organ toxicity - repeated exposure, category 1
Asp. Tox. 1	Aspiration hazard, category 1
Eye Irrit. 2	Eye irritation, category 2
Skin Irrit. 2	Skin irritation, category 2
Skin Sens. 1	Skin sensitization, category 1
STOT SE 3	Specific target organ toxicity - single exposure, category 3
Aquatic Chronic 2	Hazardous to the aquatic environment, chronic toxicity, category 2
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H332	Harmful if inhaled.
H372	Causes damage to organs through prolonged or repeated exposure.
H304	May be fatal if swallowed and enters airways.
H319	Causes serious eye irritation.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE NUMBER: Identifier in ESIS (European archive of existing substances)
- CLP: EC Regulation 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX NUMBER: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: EC Regulation 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA STEL: Short-term exposure limit

# 33178 - RESTAURO

# 33178 Madder (Alizarin) Deep

Revision nr.5 Dated 15/11/2018 Printed on 15/11/2018 Page n. 10 / 10 Replaced revision:4 (Dated 14/09/2018)

# SECTION 16. Other information ..../>>

- TWA: Time-weighted average exposure limit- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

- 1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
- 2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
- 3. Regulation (EU) 790/2009 (I Atp. CLP) of the European Parliament
- 4. Regulation (EU) 2015/830 of the European Parliament
- 5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
- 6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
- 7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
- 8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
- 9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
- 10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
- 11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
- 12. Regulation (EU) 2016/1179 (IX Atp. CLP)
- 13. Regulation (EU) 2017/776 (X Atp. CLP)
- The Merck Index. 10th Edition
- Handling Chemical Safety
- INRS Fiche Toxicologique (toxicological sheet)
- Patty Industrial Hygiene and Toxicology
- N.I. Sax Dangerous properties of Industrial Materials-7, 1989 Edition
- IFA GESTIS website
- ECHA website
- Database of SDS models for chemicals Ministry of Health and ISS (Istituto Superiore di Sanità) Italy

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses. Provide appointed staff with adequate training on how to use chemical products.

Changes to previous review: The following sections were modified: 02 / 03 / 09 / 11 / 12.