

Safety Data Sheet

According to regulation (EC) No. 1907/2006 (REACH)



944102 Liquid Stain Solvent Brown 43

Page 1

Revised edition: 22.02.2022

Version: 1

Printed: 11.04.2022

1. Identification of the Substance/Mixture and of the Company/Undertaking

1.1. Product Identifier

Product Name: Liquid Stain Solvent Brown 43

Article No.: 944102

UFI: --

1.2. Relevant identified Uses of the Substance or Mixture and Uses advised against

Identified uses:
Coloring agent

Uses advised against:

1.3. Details of the Supplier of the Safety Data Sheet (Producer/Importer)

Company: Kremer Pigmente GmbH & Co. KG

Address: Hauptstr. 41-47, 88317 Aichstetten, Germany

Tel./Fax.: Tel +49 7565 914480, Fax +49 7565 1606

Internet: www.kremer-pigmente.com

E-Mail: info@kremer-pigmente.com

Importer: --

1.4. Emergency No.

Emergency No.: +49 7565 914480 (Mon-Fri 8:00 - 17:00)

1.4.2 Poison Center:

2. Hazards Identification

2.1. Classification of the Substance or Mixture

Classification according to Regulation (EC) No. 1272/2008 (CLP/GHS)

Flammable liquids, hazard category 3
Skin sensitization, hazard category 1
Specific Target Organ Toxicity (single exposure), hazard category 3
Hazardous to the aquatic environment, chronic hazard category 3
Flammable liquid and vapour.

H226
Cat.: 3
H317
Cat.: 1

May cause an allergic skin reaction.

H336
Cat.: 3

May cause drowsiness or dizziness.

H412
Cat.: 3

Harmful to aquatic life with long lasting effects.

Possible Environmental Effects:

2.2. Label Elements

Classification according to Regulation (EC) No. 1272/2008 (CLP/GHS)

Hazard designation:

next page: 2

Safety Data Sheet

According to regulation (EC) No. 1907/2006 (REACH)



944102 Liquid Stain Solvent Brown 43

Page 2

Revised edition: 22.02.2022

Version: 1

Printed: 11.04.2022



GHS02-1



GHS07

Signal word:

Warning

Hazard designation:

H226	Flammable liquid and vapour.
H317	May cause an allergic skin reaction.
H336	May cause drowsiness or dizziness.
H412	Harmful to aquatic life with long lasting effects.

Safety designation:

P210	Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking.
P273	Avoid release to the environment.
P302+P352	If on skin: Wash with soap and water.
P312	Call a poison center or physician if you feel unwell.
P333+P313	If skin irritation or rash occurs: Get medical attention.
P501	Dispose of contents/ container according to regional, national and international regulations.

Hazardous components for labelling:

1-Methoxy-2-propanol

2.3. Other Hazards

The product is combustible and can be ignited by potential sources of ignition.

3. Composition/Information on Ingredients

3.1. Substance

3.2. Mixture

Chemical Characterization: Solvent dye in methoxypropanol. Contains Solvent Brown 43.

Information on Components / Hazardous Ingredients:

Reaction mass of Chromate(1-), [2-(3-chlorophenyl)-2,4-dihydro-4-[[2-hydroxy-5-(methylsulfonyl)phenyl]azo]-... (H302-400-410); REACH Reg. No. 01-2120764855-40	2 - 5 %	CAS-Nr: EINECS-Nr: 915-704-1 EC-Nr:
--	---------	---

1-Methoxypropane-2-ol (H226-336); REACH Reg. No. 01-2119457435-35-xxxx	< 95 %	CAS-Nr: 107-98-2 EINECS-Nr: 203-539-1 EC-Nr: 603-064-00-3
--	--------	---

Additional information:

4. First Aid Measures

4.1. Description of the First Aid Measures

next page: 3

Safety Data Sheet

According to regulation (EC) No. 1907/2006 (REACH)



944102 Liquid Stain Solvent Brown 43

Page 3

Revised edition: 22.02.2022

Version: 1

Printed: 11.04.2022

General information:

Remove contaminated clothes immediately.

After inhalation:

Supply fresh air.

In case breathing is not regular or if it has stopped, seek medical advice immediately and initiate first aid measures.

After skin contact:

Wash off immediately with soap and plenty of water and rinse thoroughly.

Remove contaminated clothing.

After eye contact:

Remove contact lens. Rinse open eyes with plenty of water (10-15 min). Should irritation continue, seek medical advice.

After ingestion:

Rinse mouth with water and drink plenty of water.

Do not induce vomiting. Consult physician immediately.

4.2. Most important Symptoms and Effects, both Acute and Delayed

Symptoms:

Narcotic effects, breathing difficulties, headache, dizziness.

Effects:

No further information available.

4.3. Indication of any Immediate Medical Attention and special Treatment needed

Treatment:

Subsequent observation for pneumonia and pulmonary edema. Monitor the circulation.

5. Fire-Fighting Measures

5.1. Extinguishing Media

Suitable extinguishing media:

Foam, carbon dioxide (CO₂), extinguishing powder, sand, water spray jet.

Unsuitable extinguishing media:

Never apply a strong water jet.

5.2. Special Hazards arising from the Substance or Mixture

Special hazards:

Fumes can form an explosive mixture with air.

In case of fire: formation of carbon oxides.

The vapor is heavier than air, spreads along the ground and distant ignition is possible.

5.3. Advice for Firefighters

Protective equipment:

Wear self-contained respiratory protective device and full protective gear.

Further information:

Cool closed containers exposed to fire with water mist.

Safety Data Sheet

According to regulation (EC) No. 1907/2006 (REACH)



944102 Liquid Stain Solvent Brown 43

Page 4

Revised edition: 22.02.2022

Version: 1

Printed: 11.04.2022

*Risk of bursting of closed containers due to strong heating.
Contaminated extinguishing water and debris should be disposed
of according to local regulations.*

6. Accidental Release Measures

6.1. Personal Precautions, Protective Equipment and Emergency Procedures

Personal precautions:

*Wear appropriate protective equipment. Keep spectators away.
Close leaks without taking any risk.
Provide adequate ventilation. Keep away from sources of ignition.
Avoid contact with skin and eyes. Do not ingest or inhale.*

6.2. Environmental Precautions

Environmental precautions:

*Do not discharge into drains, surface or ground water in
concentrated form.
Contact local authorities if product pollutes soil or vegetation.*

6.3. Methods and Material for Containment and Cleaning Up

Methods and material:

*Contain with non-flammable absorbent material (e.g. sand,
diatomaceous earth, vermiculite) and dispose accordingly.*

6.4. Reference to other Sections

*Protective clothing, see Section 8.
See Section 13 for information on disposal.*

7. Handling and Storage

7.1. Precautions for Safe Handling

Instructions on safe handling:

*Keep containers tightly closed.
Provide adequate ventilation.
Provide adequate ventilation, also in floor area (vapors are heavier
than air).*

Hygienic measures:

*Keep away from foodstuffs and drinks. Do not eat, drink or smoke
during work. Wash hands before breaks and at the end of work.
Avoid contact with eyes and skin.
Take off contaminated clothing immediately.*

7.2. Conditions for Safe Storage, including any Incompatibilities

Storage conditions:

*Store product in a cool and well ventilated area.
Store in tightly sealed containers in a dry and cool room.*

*Requirements for storage areas and
containers:*

*Store the product in the original container.
Store in a room with a solvent-proof floor.
Unsuitable container material: aluminum, light metal.
Suitable packaging: only approved packagings may be used.*

next page: 5

Safety Data Sheet

According to regulation (EC) No. 1907/2006 (REACH)



944102 Liquid Stain Solvent Brown 43

Page 5

Revised edition: 22.02.2022

Version: 1

Printed: 11.04.2022

Information on fire and explosion protection:

Keep away from sources of heat and ignition - do not smoke.
Vapors may form an explosive mixture with air. Vapor is heavier than air and spreads along the ground.
Do not store near open fires, sparks or strong oxidizing agents.
Take measures to prevent electrostatic discharge.
Do not store together with combustible, self-ignitable and flammable products, nor with highly inflammable solids.

Storage class:

3; Flammable liquids (TRGS 510)

Further Information:

7.3. Specific End Use(s)

Further information:

8. Exposure Controls/Personal Protection

8.1. Parameters to be Controlled

Parameters to be controlled (DE):

TRGS 900

1-Methoxypropane-2-ol (CAS 107-98-2): TLV (D): 370 mg/m³, 100 ml/m³; 2(l); DFG; Y

Parameters to be controlled:

1-Methoxypropane-2-ol (CAS 107-98-2), IOELV (EU): Short term value: 568 mg/m³, 150 ppm; Longterm value: 375 mg/m³; 100 ppm; skin.

1-Methoxypropane-2-ol (CAS 107-98-2): IOELV (CH): Short term value: 720 mg/m³, 200 ppm; Longterm value: 360 mg/m³; 100 ppm

1-Methoxypropane-2-ol (CAS 107-98-2): GKV (AT): Longterm value: 187 mg/m³; 50 ppm

Derived No-Effect Level (DNEL):

1-Methoxypropane-2-ol (CAS 107-98-2):

553.5 mg/m³ (worker, inhalation, short-term exposure - local effect)

396 mg/m³ (worker, inhalation, long-term exposure - systemic effects)

183 mg/kg (worker, skin contact, long-term exposure - systemic effects)

Predicted No-Effect Concentration (PNEC):

1-Methoxypropane-2-ol (CAS 107-98-2):

Fresh water: 6.83 mg/l

Seawater: 0.683 mg/l

Fresh water sediment: 52.3 mg/kg

Seawater sediment: 5.2 mg/kg

Soil: 4.59 mg/kg

Sewage treatment system (STP): 100 mg/l

Water: 100 mg/l

Safety Data Sheet

According to regulation (EC) No. 1907/2006 (REACH)



944102 Liquid Stain Solvent Brown 43

Page 6

Revised edition: 22.02.2022

Version: 1

Printed: 11.04.2022

Additional Information:

Biological limit value:

*1-Methoxypropane-2-ol: 15 mg/l (end of exposure or shift; urine)
(TRGS 203, DE)*

1-Methoxypropane-2-ol: 20 mg/l (SUVA, CH)

8.2. Exposure Controls

Technical protective measures:

No further measures, see Section 7.

Personal Protection

General protective measures:

Avoid contact with skin and avoid inhalation of vapour. Do not eat, drink or smoke while working.

Remove contaminated clothing immediately.

Do not inhale gas/fumes/vapor/aerosol.

Respiratory protection:

Required in case of insufficient ventilation.

Hand protection:

Chemical protective gloves (EN 374 (Europe), F739 (US)).

Protective gloves should be changed regularly, especially after intensive contact with the product.

Protective glove material:

Butyl rubber (480 min, 0.7 mm)

For short-term exposure (splash protection): butyl rubber gloves.

Eye protection:

Tightly fitting safety goggles (EN 166).

Body protection:

Protective clothing.

Environmental precautions:

Avoid contamination of sewage system, open water ways and ground water.

9. Physical and Chemical Properties

9.1. Information on Basic Physical and Chemical Properties

Form: liquid

Color: brown

Odor: like ether

*Odor threshold:
no information available*

*pH-Value:
not determined*

*Melting temperature:
not determined*

Boiling temperature:

next page: 7

Safety Data Sheet

According to regulation (EC) No. 1907/2006 (REACH)



944102 Liquid Stain Solvent Brown 43

Page 7

Revised edition: 22.02.2022

Version: 1

Printed: 11.04.2022

not determined

Flash point: > 21°C

Evaporation rate:
No information available.

Flammability (solid, gas):
Flammable liquid according to GHS criteria

Upper explosion limit:
no information available

Lower explosion limit:
no information available

Vapor pressure:
not determined

Vapor density:
No information available.

Density:
not determined

Solubility in water: *not determined*

Coefficient of variation (n-Octanol/Water):
not determined

Auto-ignition temperature:
not determined

Decomposition temperature:
No data available.

Viscosity, dynamic:
not determined

Explosive properties:
Product is not explosive; however, an explosive vapor/air mixture can be formed.

Oxidizing properties:
no information available

Bulk density:
not determined

9.2. Further Information

Solubility in solvents:

Viscosity, kinematic:

Burning class:

Solvent content:

Solid content:

Particle size:

next page: 8

Safety Data Sheet

According to regulation (EC) No. 1907/2006 (REACH)



944102 Liquid Stain Solvent Brown 43

Page 8

Revised edition: 22.02.2022

Version: 1

Printed: 11.04.2022

Other information:

10. Stability and Reactivity

10.1. Reactivity

*Stable if used according to specifications.
When heated: risk of ignition.*

10.2. Chemical Stability

Stable if used according to specifications.

10.3. Possibility of Hazardous Reactions

Formation of explosive vapor-air-mixtures possible.

10.4. Conditions to Avoid

Conditions to avoid:

Avoid heat, hot surfaces, sparks, naked flames and other ignition sources. Do not smoke.

Thermal decomposition:

10.5. Incompatible Materials

Oxidizing agents.

10.6. Hazardous Decomposition Products

In case of fire: formation of carbon oxides.

10.7. Further Information

11. Toxicological Information

11.1. Information on Toxicological Effects

Not classified as acute toxic. May be harmful when swallowed.

Acute Toxicity

LD50, oral:

1-Methoxypropane-2-ol: 4277 mg/kg (rat)

LD50, dermal:

1-Methoxypropane-2-ol: > 2000 mg/kg (rat)

LC50, inhalation:

No information available.

Primary effects

Irritant effect on skin:

Non irritating

Irritant effect on eyes:

Non-irritating to eyes

Inhalation:

No information available.

Ingestion:

No information available

Sensitization:

No sensitizing effect (guinea pig).

Mutagenicity:

next page: 9

Safety Data Sheet

According to regulation (EC) No. 1907/2006 (REACH)



944102 Liquid Stain Solvent Brown 43

Page 9

Revised edition: 22.02.2022

Version: 1

Printed: 11.04.2022

Not mutagenic.

Reproductive toxicity:

No reproductive toxicity expected.

Carcinogenicity:

Not cancerogenic.

Teratogenicity:

No teratogenic effects expected.

Specific target organ toxicity (STOT):

Single exposure: may cause drowsiness or dizziness.

Repeated exposure: the substance or mixture is not classified as specific target organ toxicant.

Additional toxicological information:

Aspiration hazard: not applicable

12. Ecological Information

12.1. Aquatic Toxicity

1-Methoxypropane-2-ol (CAS 107-98-2)

Fish toxicity:

LC50: < 10000 mg/l (96h, fish)

Daphnia toxicity:

No information available.

Bacteria toxicity:

No data available.

Algae toxicity:

ErC50: > 1000 mg/l (7d, Pseudokirchneriella subcapitata)

12.2. Persistency and Degradability

Readily biodegradable.

DOC Reduction: 96 % (28d)

12.3. Bioaccumulation

log KOW: < 1

12.4. Mobility

No information available.

12.5. Results of PBT- und vPvP Assessment

This substance is not classified as PBT (persistent, bioaccumulative, toxic), nor as vPvB (very persistent, very bioaccumulative).

12.6. Other Adverse Effects

Water hazard class:

1 (German Regulation) (Assessment by list): slightly hazardous.

Behaviour in sewage systems:

Further ecological effects:

Do not let product enter waterways or sewage system.

AOX Value:

next page: 10

Safety Data Sheet

According to regulation (EC) No. 1907/2006 (REACH)



944102 Liquid Stain Solvent Brown 43

Page 10

Revised edition: 22.02.2022

Version: 1

Printed: 11.04.2022

13. Disposal Considerations

13.1. Waste Treatment Methods

Product:

*Dispose of according to official national and local regulations.
If possible reuse product.*

European Waste Code (EWC):

The waste code must be determined together with the regional disposal service.

Uncleaned packaging:

Empty containers should be taken to an approved waste handling site for recycling or disposal.

*Do not puncture, cut or weld uncleaned drums. Risk of explosion.
Dispose of according to official local regulations.*

Waste Code No.:

14. Transport Information

14.1. UN Number

ADR, IMDG, IATA 1263

14.2. UN Proper Shipping Name

ADR/RID: FARBE

IMDG/IATA: PAINT

14.3. Transport Hazard Classes

ADR Class: 3

Hazard no.: 3

Classification code: F1

Tunnel restriction code: D/E

IMDG Class (sea): 3

Hazard no.: 3

EmS No.: F-E, S-E

IATA Class: 3

Hazard no.: 3

14.4. Packaging Group

ADR/RID: III

IMDG: III

IATA: III

14.5. Environmental Hazards

Not classified as environmentally hazardous.

14.6. Special Precautions for User

not applicable

next page: 11

Safety Data Sheet

According to regulation (EC) No. 1907/2006 (REACH)



944102 Liquid Stain Solvent Brown 43

Page 11

Revised edition: 22.02.2022

Version: 1

Printed: 11.04.2022

14.7. Transportation in Bulk according to Annex II of MARPOL 73/78 and IBC-Code

IMDG: not applicable

14.8. Further Information

15. Regulatory Information

15.1. Safety, Health and Environmental Regulations/Legislation specific for the Substance or Mixture

Water hazard class:

1, slightly hazardous for water (German Regulation)

Local regulations on chemical accidents:

Employment restrictions:

Restriction and prohibition of application:

Technical instructions on air quality:

15.2. Chemical Safety Assessment

A Chemical Safety Assessment has not been carried out for this product.

15.3. Further Information

16. Other Information

This product should be stored, handled and used in accordance with good hygiene practices and in conformity with any legal regulations. This information contained herein is based on the present state of knowledge and is intended to describe our product from the point of view of safety requirements. It should be therefore not be construed as guaranteeing specific properties.