According to regulation (EC) No. 1907/2006 (REACH)



# 944202 Liquid Stain Solvent Black 27

Page 1

Revised edition: 23.02.2022 Version: 1 Printed: 07.04.2022

## 1. Identification of the Substance/Mixture and of the Company/Undertaking

1. 1. Product Identifier

Product Name: Liquid Stain Solvent Black 27

Article No.: 944202

UFI: -

1. 2. Relevant identified Uses of the Substance or Mixture and Uses advised against

Identified uses:

Coloring agent

Uses advised against:

1. 3. Details of the Supplier of the Safety Data Sheet (Producer/Importer)

Company: Kremer Pigmente GmbH & Co. KG

Address: Hauptstr. 41-47, 88317 Aichstetten, Germany

Tel./Fax.: Tel +49 7565 914480, Fax +49 7565 1606

Internet: www.kremer-pigmente.com

EMail: info@kremer-pigmente.com

Importer: --

1. 4. Emergency No.

Emergency No.: +49 7565 914480 (Mon-Fri 8:00 - 17:00)

1. 4. 2 Poison Center:

#### 2. Hazards Identification

### 2. 1. Classification of the Substance or Mixture

Classification according to Regulation (EC) No. 1272/2008 (CLP/GHS)

Flammable liquids, hazard category 3 Skin sensitization, hazard category 1

Specific Target Organ Toxicity (single exposure), hazard category

3

Reproductive toxicity, hazard category 1A

H226 Flammable liquid and vapour.

Cat.: 3

H317 May cause an allergic skin reaction.

Cat.: 1

H336 May cause drowsiness or dizziness.

Cat.: 3

H360D May damage the unborn child.

Cat.: Repr. 1A

Possible Environmental Effects:

#### 2. 2. Label Elements

Classification according to Regulation (EC) No. 1272/2008 (CLP/GHS)

Hazard designation:

According to regulation (EC) No. 1907/2006 (REACH)



# 944202 Liquid Stain Solvent Black 27

Page 2

Revised edition: 23.02.2022 Version: 1 Printed: 07.04.2022

GHS02



GHS07



GHS08-2

Signal word:

Danger

Hazard designation:

H226 Flammable liquid and vapour.
 H317 May cause an allergic skin reaction.
 H336 May cause drowsiness or dizziness.
 H360D May damage the unborn child.

Safety designation:

P210 Keep away from heat/ sparks/ open flames/ hot surfaces. No

smoking.

P302+P352 If on skin: Wash with soap and water.

P312 Call a poison center or physician if you feel unwell.
P333+P313 If skin irritation or rash occurs: Get medical attention.

P501 Dispose of contents/ container according to regional, national and

international regulations.

Hazardous components for labelling:

1-Methoxy-2-propanol

2. 3. Other Hazards

The product is combustible and can be ignited by potential sources

of ignition.

### 3. Composition/Information on Ingredients

### 3. 1. Substance

#### 3. 2. Mixture

Chemical Characterization: Solvent dye in methoxypropanol

Information on Components / Hazardous

Ingredients:

C.I. Solvent Black 27 (H317-360D-373), REACH

Reg. No. 01-2020764854-42

2 - 5 % CAS-Nr:

EINECS-Nr: 939-191-9

EC-Nr:

1-Methoxypropane-2-ol (H226-336); REACH Reg.

No. 01-2119457435-35-xxxx

> 95 % CAS-Nr: 107-98-2

EINECS-Nr: 203-539-1 EC-Nr: 603-064-00-3

Additional information:

First Aid Measures next page: 3

According to regulation (EC) No. 1907/2006 (REACH)



# 944202 Liquid Stain Solvent Black 27

Page 3

Revised edition: 23.02.2022 Version: 1 Printed: 07.04.2022

4.

4. 1. Description of the First Aid Measures

General information:

Remove contaminated clothes immediately.

After inhalation:

Supply fresh air.

In case breathing is not regular or if it has stopped, seek medical

advice immediately and initiate first aid measures.

After skin contact:

Wash off immediately with soap and plenty of water and rinse

thoroughly.

Remove contaminated clothing.

After eye contact:

Remove contact lens. Rinse open eyes with plenty of water (10-15

min). Should irritation continue, seek medical advice.

After ingestion:

Rinse mouth with water and drink plenty of water.

Do not induce vomiting. Consult physician immediately.

4. 2. Most important Symptoms and Effects, both Acute and Delayed

Symptoms:

Narcotic effects, breathing difficulties, headache, dizziness.

Effects:

No further information available.

4. 3. Indication of any Immediate Medical Attention and special Treatment needed

Treatment:

Subsequent observation for pneumonia and pulmonary edema.

Monitor the circulation.

5. Fire-Fighting Measures

5. 1. Extinguishing Media

Suitable extinguishing media:

Foam, carbon dioxide (CO2), extinguishing powder, sand, water

spray jet.

Unsuitable extinguishing media:

Never apply a strong water jet.

5. 2. Special Hazards arising from the Substance or Mixture

Special hazards:

In case of fire: formation of carbon oxides.

Fumes can form an explosive mixture with air.

The vapor is heavier than air, spreads along the ground and

distant ignition is possible.

5. 3. Advice for Firefighters

Protective equipment:

Wear self-contained respiratory protective device and full

next page:

According to regulation (EC) No. 1907/2006 (REACH)



# 944202 Liquid Stain Solvent Black 27

Page 4

Revised edition: 23.02.2022 Version: 1 Printed: 07.04.2022

protective gear.

Further information:

Cool closed containers exposed to fire with water mist.

Risk of bursting of closed containers due to strong heating.

Contaminated extinguishing water and debris should be disposed of according to local regulations.

#### 6. Accidential Release Measures

#### 6. 1. Personal Precautions, Protective Equipment and Emergency Procedures

Personal precautions:

Wear appropriate protective equipment. Keep spectators away.

Close leaks without taking any risk.

Provide adequate ventilation. Keep away from sources of ignition.

Avoid contact with skin and eyes. Do not ingest or inhale.

### 6. 2. Environmental Precautions

Environmental precautions:

Do not discharge into drains, surface or ground water in

concentrated form.

Contact local authorities if product pollutes soil or vegetation.

### 6. 3. Methods and Material for Containment and Cleaning Up

Methods and material:

Contain with non-flammable absorbent material (e.g. sand, diatomaceous earth, vermiculite) and dispose accordingly.

#### 6. 4. Reference to other Sections

Protective clothing, see Section 8.

See Section 13 for information on disposal.

## 7. Handling and Storage

#### 7. 1. Precautions for Safe Handling

Instructions on safe handling:

Keep containers tightly closed. Provide adequate ventilation.

Provide adequate ventilation, also in floor area (vapors are heavier

than air).

Hygienic measures:

Keep away from foodstuffs and drinks. Do not eat, drink or smoke during work. Wash hands before breaks and at the end of work.

Avoid contact with eyes and skin.

Take off contaminated clothing immediately.

#### 7. 2. Conditions for Safe Storage, including any Incompatibilities

Storage conditions:

Store product in a cool and well ventilated area.

Store in tightly sealed containers in a dry and cool room.

Requirements for storage areas and

containers:

Store the product in the original container.



# 944202 Liquid Stain Solvent Black 27

Page 5

Revised edition: 23.02.2022 Version: 1 Printed: 07.04.2022

Store in a room with a solvent-proof floor.

Suitable packaging: only approved packagings may be used.

Unsuitable container material: aluminum, light metal.

Information on fire and explosion protection:

Keep away from sources of heat and ignition - do not smoke.

Vapors may form an explosive mixture with air. Vapor is heavier

than air and spreads along the ground.

Do not store near open fires, sparks or strong oxidizing agents.

Take measures to prevent electrostatic discharge.

Do not store together with combustible, self-ignitable and flammable products, nor with highly inflammable solids.

Storage class:

3; Flammable liquids (TRGS 510)

Further Information:

#### 7. 3. Specific End Use(s)

Further information:

## 8. Exposure Controls/Personal Protection

#### 8. 1. Parameters to be Controlled

Parameters to be controlled (DE):

TRGS 900

1-Methoxypropane-2-ol (CAS 107-98-2): TLV (D): 370 mg/m3, 100

ml/m3; 2(I); DFG; Y

Parameters to be controlled:

1-Methoxypropane-2-ol (CAS 107-98-2), IOELV (EU): Short term

value: 568 mg/m3, 150 ppm; Longterm value: 375 mg/m3; 100

ppm; skin.

1-Methoxypropane-2-ol (CAS 107-98-2): IOELV (CH): Short term

value: 720 mg/m3, 200 ppm; Longterm value: 360 mg/m3; 100

ppm

1-Methoxypropane-2-ol (CAS 107-98-2): GKV (AT): Longterm

value: 187 mg/m3; 50 ppm

Derived No-Effect Level (DNEL):

1-Methoxypropane-2-ol (CAS 107-98-2):

553.5 mg/m3 (worker, inhalation, short-term exposure - local

effect)

396 mg/m3 (worker, inhalation, long-term exposure - systemic

effects)

183 mg/kg (worker, skin contact, long-term exposure - systemic

effects)

Predicted No-Effect Concentration (PNEC):

1-Methoxypropane-2-ol (CAS 107-98-2):

Fresh water: 6.83 mg/l Seawater: 0.683 mg/l

Fresh water sediment: 52.3 mg/kg Seawater sediment: 5.2 mg/kg

According to regulation (EC) No. 1907/2006 (REACH)



# 944202 Liquid Stain Solvent Black 27

Page 6

Revised edition: 23.02.2022 Version: 1 Printed: 07.04.2022

Soil: 4.59 mg/kg Water: 100 mg/l

Sewage treatment system (STP): 100 mg/l

Additional Information:

Biological limit value:

1-Methoxypropane-2-ol: 15 mg/l (end of exposure or shift; urine)

(TRGS 203, DE)

1-Methoxypropane-2-ol: 20 mg/l (SUVA, CH)

8. 2. Exposure Controls

Technical protective measures:

No further measures, see Section 7.

Personal Protection

General protective measures:

Avoid contact with skin and avoid inhalation of vapour. Do not eat,

drink or smoke while working.

Remove contaminated clothing immediately. Do not inhale gas/fumes/vapor/aerosol.

Respiratory protection:

Required in case of insufficient ventilation.

Hand protection:

Chemical protective gloves (EN 374 (Europe), F739 (US)). Protective gloves should be changed regularly, especially after

intensive contact with the product.

Protective glove material:

Butyl rubber (480 min, 0.7 mm)

For short-term exposure (splash protection): butyl rubber gloves.

Eye protection:

Tightly fitting safety goggles (EN 166).

Body protection:

Protective clothing.

Environmental precautions:

Avoid contamination of sewage system, open water ways and

ground water.

### 9. Physical and Chemical Properties

#### 9. 1. Information on Basic Physical and Chemical Properties

Form: liquid
Color: black

Odor threshold:

no information available

pH-Value:

Odor:

not determined

odorless

According to regulation (EC) No. 1907/2006 (REACH)



# 944202 Liquid Stain Solvent Black 27

Page 7

Revised edition: 23.02.2022 Version: 1 Printed: 07.04.2022

Melting temperature:

not determined

Boiling temperature:

not determined

Flash point: > 21°C

Evaporation rate:

No information available.

Flammability (solid, gas):

Flammable liquid according to GHS criteria

Upper explosion limit:

no information available

Lower explosion limit:

no information available

Vapor pressure:

not determined

Vapor density:

No information available.

Density:

not determined

Solubility in water: not determined

Coefficient of variation (n-

Octanol/Water):

no information available

Auto-ignition temperature:

not determined

Decomposition temperature:

No data available.

Viscosity, dynamic:

not available

Explosive properties:

Product is not explosive; however, an explosive vapor/air mixture

can be formed.

Oxidizing properties:

no information available

Bulk density:

not determined

9. 2. Further Information

Solubility in solvents:

Viscosity, kinematic:

Burning class:

Inhalation:

According to regulation (EC) No. 1907/2006 (REACH)



# 944202 Liquid Stain Solvent Black 27

Page 8 Printed: 07.04.2022 Revised edition: 23.02.2022 Version: 1 Solvent content: Solid content: Particle size: Other information: 10. Stability and Reactivity 10.1. Reactivity Stable if used according to specifications. When heated: risk of ignition. 10.2. **Chemical Stability** Stable if used according to specifications. 10.3. **Possibility of Hazardous Reactions** Formation of explosive vapor-air-mixtures possible. 10.4. **Conditions to Avoid** Conditions to avoid: Avoid heat, hot surfaces, sparks, naked flames and other ignition sources. Do not smoke. Thermal decomposition: 10.5. **Imcompatible Materials** Oxidizing agents. 10.6. **Hazardous Decomposition Products** In case of fire: formation of carbon oxides. 10.7. **Further Information** 11. **Toxicological Information** 11. 1. Information on Toxicological Effects Not classified as acute toxic. May be harmful when swallowed. Acute Toxicity LD50, oral: 1-Methoxypropane-2-ol: 4277 mg/kg (rat) C.I. Solvent Black 27: LD50: > 10000 mg/kg (rat; BASF) LD50, dermal: 1-Methoxypropane-2-ol: > 2000 mg/kg (rat) C.I. Solvent Black 27: LD50: > 2000 mg/kg (rat; OECD 402) LC50, inhalation: No information available. Primary effects Irritant effect on skin: Non irritating Irritant effect on eyes: Non-irritating to eyes

No information available.

According to regulation (EC) No. 1907/2006 (REACH)



#### **Liquid Stain Solvent Black 27** 944202

Page 9

Revised edition: 23.02.2022 Version: 1 Printed: 07.04.2022

Ingestion:

No information available

Sensitization:

No sensitizing effect (guinea pig).

Mutagenicity:

Not mutagenic.

Reproductive toxicity:

No reproductive toxicity expected.

Carcinogenicity:

Not cancerogenic.

Teratogenicity:

No teratogenic effects expected.

Specific target organ toxicity (STOT):

Single exposure: may cause drowsiness or dizziness.

Repeated exposure: the substance or mixture is not classified as

specific target organ toxicant.

Additional toxicological information:

Aspiration hazard: not applicable

#### 12. **Ecological Information**

#### 12. 1. **Aquatic Toxicity**

Fish toxicity:

1-Methoxy-2-propanol: LC50: < 10000 mg/l (96h, fish)

C.I. Solvent Black 27: LL50: >100 mg/l (96h, Danio Rerio; OECD

203)

Daphnia toxicity:

C.I. Solvent Black 27: EL50: >100 mg/l (48h, Daphnia Magna;

OECD 202)

Bacteria toxicity:

C.I. Solvent Black 27: EC10: 100 mg/l (3h, active sludge; OECD

209)

Algae toxicity:

1-Methoxy-2-propanol: ErC50: > 1000 mg/l (7d,

Pseudokirchneriella subcapitata)

12. 2. Persistency and Degradability

Readily biodegradable.

DOC Reduction: 96 % (28d)

12.3. Bioaccumulation

log KOW: < 1

12.4. Mobility

No information available.

12. 5. Results of PBT- und vPvP Assessment

> This substance is not classified as PBT (persistent, bioaccumulative, toxic), nor as vPvB (very persistent, very

Hazard no .:

According to regulation (EC) No. 1907/2006 (REACH)



# 944202 Liquid Stain Solvent Black 27

Page 10 Revised edition: 23.02.2022 Printed: 07.04.2022 Version: 1 bioaccumulative). 12. 6. Other Adverse Effects Water hazard class: 1 (German Regulation) (Assessment by list): slightly hazardous. Behaviour in sewage systems: Further ecological effects: Do not let product enter waterways or sewage system. AOX Value: 13. **Disposal Considerations** 13. 1. Waste Treatment Methods Product: Dispose of according to official national and local regulations. If possible reuse product. European Waste Code (EWC): The waste code must be determined together with the regional disposal service. Uncleaned packaging: Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not puncture, cut or weld uncleaned drums. Risk of explosion. Dispose of according to official local regulations. Waste Code No.: 14. **Transport Information** 14. 1. **UN Number** ADR, IMDG, IATA 1263 14. 2. **UN Proper Shipping Name** ADR/RID: **FARBE** IMDG/IATA: **PAINT** 14. 3. **Transport Hazard Classes** ADR Class: 3 Hazard no.: 3 Classification code: F1 Tunnel restriction code: D/E IMDG Class (sea): 3 Hazard no.: EmS No.: F-E. S-E IATA Class: 3

3

According to regulation (EC) No. 1907/2006 (REACH)



#### **Liquid Stain Solvent Black 27** 944202

Page 11

Printed: 07.04.2022 Revised edition: 23.02.2022 Version: 1

14. 4. **Packaging Group** 

> Ш ADR/RID: IMDG: Ш

IATA: Ш

14. 5. **Environmental Hazards** 

Not classified as environmentally hazardous.

14.6. **Special Precautions for User** 

not applicable

Transportation in Bulk according to Annex II of MARPOL 73/78 and IBC-Code 14.7.

IMDG: not applicable

14. 8. **Further Information** 

#### 15. **Regulatory Information**

15. 1. Safety, Health and Environmental Regulations/Legislation specific for the Substance or Mixture

Water hazard class:

1, slightly hazardous for water (German Regulation)

Local regulations on chemical accidents:

Employment restrictions:

Restriction and prohibition of application:

Technical instructions on air quality:

15. 2. **Chemical Safety Assessment** 

A Chemical Safety Assessment has not been carried out for this

product.

**Further Information** 15.3.

#### 16. Other Information

This product should be stored, handled and used in accordance with good hygiene practices and in conformity with any legal regulations. This information contained herein is based on the present state of knowledge and is intended to describe our product from the point of view of safety requirements. It should be therefore not be construed as guaranteeing specific properties.